### THRUPUT

## 4K x 2K Video Integration GF MIDAS IV

Next generation video processing technology, renders up to four videos, at the same time.

- All input and output resolutions up to 3840 x 2160.
- 4 x DVI DL inputs.
- Independent EDID (Extended Display Identification Data).
- HDMI 1.4 and DVI DL outputs.
- Any input, anywhere.
- Composite output: Cut, crop and stack inputs, with transparent overlay.



#### **Perfect rendering**


The Thruput MIDAS IV generates an 8 megapixel video stream for the new generation of 4K x 2K displays with HDMI and DVI compatible inputs.

All inputs can be rendered as single screens, or processed to create composite video presentations.

#### New possibilities

The large size and high resolution of new displays creates new possibilities for information display.

- View one 4K × 2K image across the entire screen.
- View several channels of information on one screen rather than on many separate monitors.
- Embed screens from a mix of UNIX, LINUX, Solaris or Windows sources.



# THRUPUT

## 4K x 2K Video Integration GF MIDAS IV

### Safety

Thruput True-pixel graphics processing:

- Directly maps input pixel to LCD pixel.
- Avoids any zoom engines or pixilation chipsets.
- All data channels are isolated and data from one channel cannot pass to another.

### **Green solution**

The MIDAS IV does not use any hazardous materials, and is:

- Fully RoHS compliant, with ultra-low power consumption.
- Typically 15W in normal operation.

### **Specification**

opecification	
Resolution	3840 x 2160
Inputs	4 off DVI DL
Outputs	DVI DL and HDMI 1.4 (cloned)
Function	<ul> <li>Set input and output resolutions.</li> <li>Independent EDID (Extended Display Identification Data).</li> <li>Synchronise all received data.</li> <li>Create composite output of any or all inputs</li> <li>Cut, crop, position and stack each input.</li> <li>Set transparency colours for each input.</li> </ul>
Power	Universal input voltage, worldwide use. Typically below 15W (normal operation).
Noise	0 dB (silent operation)
Weight	2.5 Kg
MTBF	127,000 hours
Compliance	CE, FCC and ROHS.
Record	Record composite output using Sentinel 4K x 2K recorder.
HMI	Option for synchronized switching of mouse & keyboard.
Extension	Up to 100m, Sentinel KVMX extender.



Thruput Limited 6 Whitworth Road, Marston Trading Estate, Frome, Somerset, BA11 4BY, UK Author: ND Date: July 2016

Office: +44 1373 300 818 Web: <u>http://www.thruput.co.uk/</u> Email: <u>sales@thruput.co.uk</u> Thruput Limited operates a policy of continuous improvement and information in this document is subject to change without notice.